

Product Data Sheet

PlasmaConnect 10

Non-Thermal Plasma for Water- and Waste Water Treatment

DESCRIPTION	<p>PlasmaConnect is an innovative and future-oriented technology for advanced oxidation based on ionized air – known as non-thermal plasma (NTP). Due to its high efficiency, easy integration, and broad effectiveness against a wide range of pollutants, C-ION™ technology sets new standards in modern water treatment. It removes even difficult-to-degrade organic substances such as drug residues, hormones, pesticides, and herbicides, and oxidizes inorganic substances such as metals (iron, manganese, and arsenic). In addition, the process has a disinfecting and decolorizing effect and contributes to a lasting improvement in the microbiological quality of water. PlasmaConnect is used in numerous areas – from wastewater and drinking water treatment to water reuse.</p>	
C-ION™ PLASMA UNIT	<p>Plasma generation: Plasma type: Dimension: Weight: Connections:</p>	<p>Dielectric barrier discharge (DBE) Non-thermal (cold) plasma 700 x 180 x 125 mm 5.5 kg Air inlet: DN40 Plasma outlet: DN40</p>
PRODUCT SPECIFICATION	<p>Number of plasma units: Piping: Frame: Dimension: Weight: Connections:</p>	<p>10 PVC-U / Stainless steel 304/304L Stainless steel 304/304L 1150 x 800 x 1959 mm approx. 250 kg Plasma outlet: DN40</p>
FEED REQUIREMENTS	<p>Temperature range: Air-Humidity:</p>	<p>4 – 40°C < 70%</p>
OPERATION INFORMATION	<p>Blower: Power supply: Power: max. Diffusor depth: max. cleaning capacity:</p>	<p>48 m³/h; 250 mbar 400V / 50Hz (3-phasing) 2.5 kW 2 m 50 m³/h*</p> <p>*depending on the degree of contamination</p>
	<p>Please also note:</p>	<p>Inlet and outlet at opposite ends of the tank to avoid short circulation Keep the plasma hose as short as possible (efficiency reduction) Connecting parts must be ozone resistant The oxidation tank must be designed as a closed system with exhaust air openings. Ozone enrichment is possible in the oxidation tank.</p>

PRODUCT HIGHLIGHTS

- Ready-to-connect base unit including control panel
- High oxidation potential (2.75 V through the formation of hydroxyl radicals, reaction rate $2.2 \cdot 10^7$ to $1.8 \cdot 10^{10}$ M⁻¹s⁻¹)
- Lower energy consumption compared to other oxidation processes, e.g., ozone
- No additional cooling required
- No special explosion or emission containment measures required
- No chemical consumables required
- No supply air treatment required
- Easy retrofitting of existing tanks possible

INCL. AERATION PACKAGE

- 10 Disc diffuser: 12" x 70 mm; 1.35 kg; connection: 1"
- 10 Concrete base plate: 320 x 220 x 70 mm; 9.6 kg; connection: 16 mm

OPTIONAL PACKAGES

- Reaction tank including level control
- System integration into building management



The information contained in this document is deemed to be accurate and reliable. Nevertheless, it should not be construed as conferring any warranty or guarantee of performance. Dimensions and membrane geometry are subject to modification due to production and process enhancements. No responsibility, obligation, or liability is assumed for any outcomes or damages resulting from the utilization of the unit.